



## BONA CARL'S 25 Sitework

### Surface preparation

Vacuum clean to remove loose dirt. Then clean the floor with a cleaner/water solution, approx. 0.2 litre Carl's Cleaner to 10 litres of water. (For further information see Carl's Cleaner.)

### Application

When the floor is absolutely dry apply a thin layer of Carl's 25 using a cotton cloth or similar. On large areas apply the oil using a buffing machine: Put the cloth on the floor, place a red pad on the cloth and pour ca 0.1 litre oil in the middle of the pad. Spread the oil evenly on ca 10 m<sup>2</sup>, add more oil as required, and continue until the whole floor surface has got a thin layer of oil. Move the machine in alternate directions and finish along the grain. On the edges and in the corners the oil should be applied by hand with a cotton cloth.

Allow the floor to dry for at least 1 hour. Afterwards buff it with a red pad under the machine. Move the machine in alternate directions and finish along the grain.

Allow the floor to dry for 12 hours without any foot traffic.

Clean the floor on a daily basis using a dry mop and/or a vacuum cleaner. When necessary, wipe off with a damp mop with Carl's Cleaner added to the cleaning water. N.B. Always clean using as dry a method as possible.

**Warning:** Carl's 25 contains drying oils. Risk of self-ignition. Used cloths, rags and similar should be placed in water or sealed metal containers.