

BONA CROSSLINKER

Product Description & Sitework



Features

Bona Crosslinker is an additive compatible with Mega and Spectra which improves properties such as adhesion and the resistance to chemicals and scuffmarks. Suitable to add to the finish in areas where more spillage and wear can be expected such as in kitchens, hallways etc. Mega must always have the addition of Crosslinker when used for overcoating purposes, Spectra is however not recommended for overcoating.

- Improves adhesion and chemical resistance in Mega and Spectra.
- Used together with Mega when overcoating previously finished surfaces.

Directions for use

The finish container and the Crosslinker are both provided with a measurement scale. After having determined the quantity of finish required, first dilute the amount of Crosslinker to be added (2%) with an equal volume of water and shake well. The mixture Crosslinker/water should then be mixed with the finish within 15 minutes and the new mixture should be carefully stirred at once. The mixture of finish/Crosslinker should be used within 8 hours.

For finishing instructions see label or sitework for Bona Mega or Bona Spectra.

Technical Data

| | |
|--------------------|---|
| Mixing ratio: | 2% Bona Crosslinker + 2% water |
| Safety: | Classified, (see Safety Data Sheet) |
| Flash point: | Non-flammable |
| Shelf life: | 1 year, from date of production, in unopened original container |
| Storage/transport: | The temperature must not fall below +5°C or exceed +25°C during storage and transport |
| Disposal: | Wastes and emptied containers should be handled in accordance with local regulations. |
| Pack size: | 12 x 100 ml (160 boxes per pallet) |